51.009N | SlipStop Ultra

An ultra-thick, heavily embossed floor graphic built to withstand wear and tear from vehicles, forklifts, and more.

FACE FILM

Polymeric PVC, clear heavy embossed

Thickness (µm)	450

ADHESIVE

Clear solvent-based acrylic, permanent

Thickness (µm)	50	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	17	
24 hours (180°) N/25mm	23	

RELEASE LINER

Lay-flat kraft paper, double-sided PE coated liner

Weight (gsm)	145

PRODUCT APPLICATION

Application method	Cold lamination (<30°C)
Application temparature (°C)	10 to 30
Service temperature (°C)	-10 to 80

DURABILITY

Shelf Life (months)	12
Durability (years)	2

CERTIFICATES

Anti-Slip Rating	R10	DIN 51130

ROLL SIZES

1370mm x 25m

Scan or click to access our Durability Guide

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.