31.100N | SlipStop Grit White

A durable, tear-resistant white PET film with a visibly rough, highly structured surface. This film holds an R13 certification, the highest anti-slip safety rating in our industry. It is typically used to create graphics and safety markings in high-risk areas where water is constantly present, such as commercial kitchens, wet industrial environments, and high-traffic wet zones.

FACE FILM

PET, fine structured white

Thickness (µm)	300	Due to the structure, the thickness may vary in different areas

ADHESIVE

Clear solvent-based acrylic, high tack permanent

Thickness (µm)	40	
Adhesion to steel		FINAT FTM 1
20 minutes (180°) N/25mm	24	
24 hours (180°) N/25mm	30	

RELEASE LINER

Lay-flat kraft paper, double-sided PE coated

Weight (gsm)	140

PRODUCT APPLICATION

Application method	Dry
Dimensional stability (.mm)	<1
Application temperature (°C)	0 to 30
Service temperature (°C)	-30 to 60

DURABILITY

Shelf life (months)	18
Indoor durability (year)	1
Outdoor durability (months)	6

CERTIFICATES

Anti-Slip rating	R13	DIN 51130
Fire rating	EN 13501-1 (Class B)	

ROLL SIZES

1370mm x 45,7 m

PRINTING METHOD

Latex, UV

Fourbases BV guarantees the material for twelve months from the date of final invoice. The shelf life of our material depends on storage conditions. The end user should store the material in the original boxes or in equivalent boxes, away from direct sunlight, at a temperature of 21°C and 50% relative humidity. Fourbases BV guarantees that the products are free from defects in workmanship or defects in iSee2 material, provided they are stored properly. At its sole discretion, Fourbases BV may either: (1) replace all or part of the materials, or (2) issue a credit note for the value of the defective portion. All quoted data values are typical and should not be used as a basis to consider the product defective if measured values differ.